

**TECHNICAL DATA SHEET – OVERVIEW***MELVILLE 80 PAVERS TEXTUREGUARD*

**Dimensions (mm):** **Poids approximatif (kg / unit)**  
(Thickness x width x length)

80 x 190 x 380	14 kg
80 x 380 x 380	28 kg
80 x 380 x 570	42 kg

Average weight per square foot : 36 kg

**Range Colours :** Marbella, Silverstone, Hickory

**Finish:** Smooth

**Physical properties**  
**(In accordance with CSA – A231.2 Precast Concrete Pavers)**

Compressive strength (min) : 50 MPa (average)  
No individual value less than 45 MPa

Durability (freeze/thaw) with de-icing salt  
- Loss of mass after 28 cycles (max) : 225 g/m<sup>2</sup>  
- Loss of mass after 49 cycles (max) : 500 g/m<sup>2</sup>

**Dimensional tolerances**

Thickness: ± 3 mm  
Length & width: -1 to + 2 mm

**Technical Services**

Technical support provided by Permacon's representatives and engineering department.  
Product samples available upon request to your sales representative.

Test report is available upon request. This report is issued after testing done by our laboratory engineers and technicians.

For information regarding the LEED certification program, please contact your representative or Permacon's engineering department.