

Vendome[®] Pavers 80

Techniseal Sand 1 Bag - Approx. 23 ft² coverage

Pedestrian - Designed to withstand pedestrian traffic

Vehicular - Designed to withstand car traffic

Permeable - Designed to allow runoff to pass through



Vendome[®] Pavers


	Dimensions (mm)	Dimensions (in)
A	80 x 130 x 197	3 1/8 x 5 1/8 x 7 3/4
B	80 x 130 x 262	3 1/8 x 5 1/8 x 10 5/16
C	80 x 130 x 327	3 1/8 x 5 1/8 x 12 7/8
Weight/unit (avg.)	6 kg	12 lb
Units/area (avg.)	30.50 units/m ²	2.83 units/ft ²
Area/layer	1.05 m ²	11.28 ft ²
Area/cube	8.40 m²	8 Rows 90.24 ft²
Qty/cube	A = 88 B = 96 C = 72	
Length/layer	7.86 lin. m	25.80 lin. ft
Length/cube	62.90 lin. m	206.40 lin. ft
Weight/cube	1468 kg	3236 lb

Colours


Codes	Colours
PRESTIGE COLOURS	
10550002	Rockland Black
10559011	Range Margaux Beige
10559012	Range Amboise Beige
STANDARD COLOURS	
10559010	Range Newport Grey

Sold in full cubes only
Production location – Bolton


Typical row



Laying Patterns



LINEAR PATTERN



MODULAR PATTERN

Notes

Setting of joint-filling sand: Cover the vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover the snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches or concrete shards.

Laying patterns: These laying patterns are by way of example only and represent only a few of many possibilities. Permacon shall not be responsible for the excess or shortage of pavers resulting from installation according to these laying patterns.

Additional details specific to this product are available by consulting our landscaping installation guide on our website (Permeable pavement section).